










## Control Handles Accessories

	<p>Flexible Extensions Flexible whip hose extensions with crimped ends Includes adapter to attach to grease control handle</p>	<p><b>8390-002</b>, 18" Whip hose HP flexible extension <b>8390-003</b>, 36" Whip hose HP flexible extension <b>8390-004</b>, 42" Whip hose HP flexible extension</p> <p>Max. pressure 5,000 psi (345 bar). Hose end 1/8" NPT(M) on both ends. Compatible fluid NLGI-2 Grease</p>
	<p>Grease Coupler Standard super grip coupler</p>	<p><b>5200-017</b> Quick Lock grease coupler 1/8" NPT(F)</p> <p><b>5310-024</b> Grease coupler, 4-jaw. Max pressure 10,000 psi (690 bar). Threads 1/8" -27 NPT. Compatible Fluid: NLGI-2 Grease</p>
	<p><b>Z-Swivel</b> Swivel action for better control Installed between grease handle and fluid hose for freedom of motion Low friction ball bearing swivels High pressure packing</p>	<p><b>5310-018</b> Z-Swivel. Max pressure 5,000 psi (345 bar). Inlets: 1/4" NPT(F) x 1/4" NPT(M). Wetted materials: Steel</p>
	<p>Shrouds Protects vehicle or machine surfaces from scratches.</p>	<p><b>833398</b> Multi Colored set; red, yellow, green, blue (4 pcs)</p>

3

### NOZZLES

	MODEL	INLET	TIP OD	MAX. FLOW	NOZZLE
	<b>3332-097</b>	1/4" NPT(F)	0.612" Verify ID of ATF fill port for compatibility	2.1 gal/min (8 l/min)	Auto
	<b>3332-096</b>	1/4" NPT(F)	0.710" Verify ID of ATF fill port for compatibility	3.7 gal/min (14 l/min)	1/4 Turn Manual for OIL ports
	<b>3332-105</b>	1/4" NPT(F)	0.312" Verify ID of ATF fill port for compatibility	3.7 gal/min (14 l/min)	1/4 Turn Manual for ATF ports
	<b>3332-090</b>	3/8" NPT(F)	0.548" Verify ID of ATF fill port for compatibility	5.0 gal/min (18.9 l/min)	Semi-Auto
	<b>3332-030</b>	1/2" NPT(F)	-	15.5 gal/min (58.79 l/min)	Semi-Auto HighFlo