


# **Control Handles DR Meter (Digital Register Meter)**



See Dispense nozzle OD for important details

TECHNICAL DATA		
Units of measure	Batch: Gallons, Quarts, Pints, and Liters (in 0.01 increments)	
Accuracy	+/- 0.5% of reading (lubricating oils)	
Flow Range	0.26-8 gal/min (1-30 l/min)	
Maximum pressure	1,450 psi (100 bar)	
Swivel inlet	1/2" NPT(F)	
Dispense Nozzle OD	Auto = 0.605"  Manual 1/4 turn for OIL = 0.705"  Manual 1/4 turn for ATF= 0.315"  Verify ID of ATF fill port for compatibility	
Operating temperature	14 °F to 140 °F (-10 °C to 60 °C)	
Weight	4 lb (1.80 kg)	
Battery	2 x 1.5 v alkaline "AAA"	
Compatible Fluids	Oil, transmission fluid, hydraulic fluid, and anti-freeze	
Wetted Materials	Liquid Crystal Polymer (LCP), aluminum, Buna-N™, zinc plated steel, stainless steel, neodymium, and brass	
Service Bulletin	SB 3095	

### Dimensions inches (mm)





833398 Multi Colored set; red, yellow, green, blue (4 pcs)



## **Features**

- Precision robotically machined aluminum die-cast fluid chamber for repeatable accuracy
- Sealed battery compartment; 2 AA batteries
- Low power consumption with auto sleep function
- Trip mode function; can operate as a simple fluid management device
- Non-resettable totalizer; maintains total volume of meter since day one
- Ergonomic comfort handle
- Unique 1/4 turn manual tip; fast, simple
- Flanged coupling; prevents leaks commonly found in competitive meters
- Swivel protective cover
- Affordable repairability

#### Fluids

- Synthetic and mineral based lubricants
- Gear Oil
- Hydraulic oil and fluids
- ATF
- Anti-freeze (Glycol) and anti-freeze water solution

## **Markets Served**

- Car and truck dealers
- Fast lube and maintenance shops
- Fleets
- Mining and construction
- Lube trucks

MODELS Available	EXTENSION TYPE & NOZZLE	EXTENSION CODE
Verify ID of ATF fill port for compatibility.		
3330-161	Flex Auto	3332-095
3330-157	Rigid 1/4 turn - OIL	3332-091
3330-158	Flex 90 1/4 turn - OIL	3332-092
3330-159	Flex-memory 1/4 turn - OIL	3332-093
3330-169	Rigid 1/4 turn - ATF	3332-101
3330-172	Flex-memory 1/4 turn - ATF	3332-104
3330-166	DR bare	-