

Ordering Information

Heavy-Duty Reinforced Lubrication Hoses

For use with grease, oil and undercoating material. Hoses are black, male connections at both ends. Lubrication hoses listed are grounded for static electrical discharge.

	ID Inch (mm)	Max PSI (bar)	Hose Length	Fitting		Part Number	
				End 1 Thread NPT(M)	End 2 Thread NPT(M)		
	1/4 (6.44)	5,000 (345)	12 in (0.3 m)	1/8	1/8	109145	
			30 in (0.8 m)			109148	
			24 in (0.8 m)	3/8	3/8	109147	
			48 in (1.2 m)	1/4	1/4	109149	
			72 in (1.8 m)			109150	
			12 ft (3.6 m)			109151	
			15 ft (4.6 m)			109152	
			20 ft (6.1 m)			3/8	109153
			25 ft (7.6 m)			1/4	109154
			35 ft (10.6 m)	3/8	3/8	109156	
			40 ft (12.2 m)			109157	
			50 ft (15.3 m)			109158	
			3/8 (9.5)	4,000 (276)	12 in (0.3 m)	1/4	1/2
	24 in (0.62 m)	3/8			3/8	109161	
	48 in (1.2 m)					109162	
	72 in (1.8 m)					109163	
	15 ft (4.6 m)	1/4			1/4	109165	
	40 ft (12.2 m)				3/8	109169	
	50 ft (15.3 m)				109170		
1/2 (12.7)	3,000 (207)	15 in (0.4 m)	1/2	1/2	110069		
		18 in (0.5 m)			220598		
		54 in (1.4 m)			220600		
		72 in (1.8 m)			220591		
		10 ft (3.1 m)			220590		
		16 ft (4.9 m)			220592		
		20 ft (6.1 m)			220593		
		25 ft (7.6 m)			220608		
		40 ft (12.2 m)			221092		
		50 ft (15.3 m)			221093		
		75 ft (22.9 m)	3/4	237861			
3/4 (19.1)	2,250 (155)	18 in (0.4 m)	3/4	3/4	109108		
		72 in (1.8 m)			109105		
		10 ft (3.0 m)			111010		
		75 ft (22.9 m)	1/2	1	237865		
		50 ft (15.2 m)			237866		
1 (25.4)	212 (14.6)	50 ft (15.2 m)	1	1	241908		
1 (25.4)	125 (8.7)	50 ft (15.2 m)	1	1	249058		