












Square Head Plug



Swivel Adapters*











Rigid End	Swivel End	Straight Swivel Adapter (m x f)	Straight Swivel Adapter (f x f)	90° Swivel Adapter (f x f)	90° Swivel (m x f)	45° Swivel Adapter (m x f)
1/8 in	1/4 in	208434	-	-	-	-
1/4 in	1/4 in	156823	155570	157676	155541	-
	3/8 in	157705	-	-	-	-
3/8 in	1/4 in	-	159153	-	155495	-
	3/8 in	155665	156173	155677	155494	161889
	1/2 in	162505	-	159801	217430	-
1/2 in	1/4 in	-	155653	-	-	-
	3/8 in	158256-257	161077	-	161037	-
	1/2 in	156684	155865	157416	155470	-
3/4 in	3/4 in	157785	156172	156589	160327	105281
1 in	3/4 in	202965	-	-	-	-
	1 in	160022	158383	-	-	-

^{*}Not a "live" swivel, position is stationary after tightened.

Tube Fittings

Maximum pressure rating of 3,000 psi (207 bar) with appropriate tubing wall thickness.

	Description	lalak	Tube OD		
		Inlet	5/8 in	7/8 in	
	Tube Union Flow 90° Elbow	=	101012	101376	
1 23	Straight Tube Union	=	101009	101340	
	Male Connector	3/4 in NPT	-	101339	
	Straight Female Connector	1/2 in NPT	101008	-	
C 1	Tube Tee with Female Branch	5/8 in NPT	101013	-	