









Oil Piston Pumps Accessories

PISTON PUMP ACCESSORIES

Bung adapters		4411-009N Bung adapter: Panther® HP & Tiger® W/ pressure relief port	Air eliminator		4411-005 Air eliminator 3/4" NPT(F) / 1 1/2" NPT(M) adapter	
		4411-009QX Bung adapter: Panther® HP W/ pressure relief port - 10 pieces			4411-010 Air eliminator 1/4" NPT(F) / 1" NPT(M) adapter	
		4411-018N Double tap bushing, zinc plated stainless steel: for use with Panther® HP W/ pressure relief	Pump runaway control prevents runaway condition when out of oil		3241-001 Pump runaway control 1/2" NPT(F)	
		4411-022 Bung adapter: LYNX® 3:1 & LYNX® 5:1			3241-002 Pump runaway control 1/4" NPT(F)	
		4411-021 Bung adapter: LYNX®: 1:1 SS, LYNX® 5:1 HD, Lion 450/600 Grease and 1 1/2" suction tube	Inlet Check Valve Aluminum		4411-014 Inlet Check Valve 3/4" NPT(F)	
		4411-012 Bung adapter kit: for use with 1" OD suction tube			4411-015 Inlet Check Valve 1" NPT(F)	
		4411-024 Bung adapter, PVC: W/ pressure relief port-2" for use when no additional ports are not available on the tank for pressure relief discharge tube			4411-038 Inlet Check Valve 1 1/2" NPT(F)	
		3120-211 1/2" NPT(F)		HP BALL VALVE		
	Couplers, strainers Y-Strainer - For filtering debris at the pump - 580 psi (40 bar) - all strainers have 40 mesh.		3120-212 3/4" NPT(F)	Ball valve fully ported		3230-023 Ball valve, 3/8", 7,250 psi (500 bar)
			3120-213 1" NPT(F)		3230-015 Ball valve, 1/2", 7,250 psi (500 bar)	
		3120-085 Pressure relief kit, 1/2" NPT(M) 850 psi for use with Panther® 3:1 and 5:1	3230-016 Ball valve, 3/4", 5,800 psi (400 bar)			
Ensure that all hose fittings and piping are rated for fluid outlet pressures. Balcrank recommends a minimum of 3 x safety factor.			MP BALL VALVES WITH OIL/AIR			
In-line pressure relief		3120-086 Pressure relief kit, 3/4" NPT(M) 850 psi for use with LYNX® 1:1, 3:1	Ball valve fully ported no bleed			3230-006 Ball valve, 3/8", 2,000 psi (138 bar)
		3120-087 Pressure relief kit, 3/4" NPT(M) 1400 psi			3230-002 Ball valve, 1/2", 2,000 psi (138 bar)	
		3120-214 Kit, PR valve 1/4" NPT(M) 850 psi for use with Lion™ 450 3:1, 6:1 and Lion™ 600 6:1, kit includes return tube and 1/8" NPT(M) adapter			3230-007 Ball valve, 3/4", 2,000 psi (138 bar)	
Pressure relief valves		3120-215 Kit, PR valve 1/4" NPT(M) 1,450 psi for use with Lion™ 450 10:1 and Lion™ 600 12:1, kit includes return tube and 1/8" NPT(M) adapter			3230-008 Ball valve, 1/4", 580 psi (40 bar)	
		3230-009 Shut-off valve, 3/8" NPT(F), 200 psi (13.7 bar)		3230-019 Ball valve, 3/8", 580 psi (40 bar)		
				LP AIR BLEED TYPE		
				Shut-off valve bleed type for air		3230-010 Shut-off valve, 1/2" NPT(F), 200 psi (13.7 bar)
						3230-011 Shut-off valve, 3/4" NPT(F), 200 psi (13.7 bar)
						3230-009 Shut-off valve, 3/8" NPT(F), 200 psi (13.7 bar)